Use carbon nanotubes/carbon composite counter electrodes as hole transport layer for efficient methylammonium lead bromide perovskite solar cells

Xiaohui Liu,Yanfang Gao,*

College of Chemical Engineering, Inner Mongolia University of Technology, Hohhot, 010051, P.R. China

* E-mail:yf_gao@imut.edu.cn

Organic–inorganic metal halide perovskites, especially methylammonium lead halide or mixed halide, have attracted significant attention as promising materials for photovoltaic applications due to their high absorption coefficients, excellent carrier transport, chemical and structural diversity, and proper band gap.[1]Most efficient perovskite solar cell devices employ organic charge transfer materials,such as an organic hole transport material (HTM) of 2,2′,7,7′-tetrakis-(N,N-di-p-methoxy phenylamine)-9,9′-bifluorene (spiro-MeOTAD) or an electron transport material of phenyl-C61-butyric acid methyl ester in combination with metal electrodes. The utilization of organic electronic components not only raises devices cost but also affects their long-team stability. Thus, it is highly desirable to develop perovskite photovoltaics which are free of organic materials.[2]

Carbon materials, due to their excellent stability, low cost and facile processability, have been used to replace the expensive HTM and noble metal electrode in perovskite solar cells and achieved reliable efficiency and impressive stability.[3]carbon nanotubes being a promising candidate due to their extraordinary electrical and mechanical properties.Here we focused different carbon materials such as commercial graphite,carbon black,commercial hard coal,biochar and active carbon,thus can find a better material for the improvement of the perovskite solar cells.

The semi-transparent,high voltage MAPbBr3/CNT solar cells will show great potential in solar cell windows, tandem solar cells and solar fuels applications.Carbon are nanotubesexcellent electronic transporting materials due to their exceptional charge transport feature as well as their chemical stability and hydrophobicity. Carbon nanotubes have become one of the promising components in perovskite solar cells.

References

[1] Da-Young Lee,Seok-In Na and Seok-Soon Kim et al.Graphene oxide/PEDOT:PSS composite hole transport layer for efficient and stable planar heterojunction perovskite solar cells[J].Nanoscale, 2016, 8, 1513–1522 | 1513.
[2]Hao Li, Kun Cao, Jin Cui, Shuangshuang Liu, Xianfeng Qiao, Yan Shen and Mingkui Wang,et al.14.7% efficient mesoscopic perovskite solar cells using single walled carbon nanotubes/carbon composite counter electrodes[J].Nanoscale, 2016, 8, 6379–6385 | 6379.
[3]Zhen Li,Pablo P. Boix,Guichuan Xing,Kunwu Fu,Sneha A. Kulkarni,Sudip K.Batabyal,Wenjing Xu,Anyuan Cao,Tze Chien Sum,Nripan Mathewsa,and Lydia Helena Wong,et al.Carbon nanotubes as an efficient hole collector for high voltage methylammonium lead bromide perovskite solar cells[J].Nanoscale, 2016, 8, 6352–6360.

Biography

Yanfang Gao has completed her PhD at the age of 30 years from Fukui University and postdoctoral studies from Tsinghua University of Chemistry. She is a professor at the department of Inner Mongolia University of Technology,a tutor of a phD student.She has published more than 20 papers in reputed journals.

Presenting author details

Full name: Xiaohui Liu
Contact number: +86 13684781428
Session name/ number: International Conference on Advanced Materials and Nanotechnology
Category: Poster presentation